

Screen shade

The FILCLAIR

Screen shade with flat roof benefits from essential constructive elements, allying simplicity of assembly and resistance to the climatic loads.

Technical characteristics

The structure, consisted of round tubes perfectly balanced for an optimized resistance, is exclusively realized in the best galvanized steels (European Standard EN-10147).

Transverse porch Ø 60 - 15/10th

Hanger Ø 32 - 15/10th

Patented telescopic Foot and muff of connection Ø 55 - 20/10th

Multiples configurations

- Screen shade in roof, banks and fronts.
- partial or total screen shade in banks and fronts.
- sliding Door of access 4,00 m in bank and front.

Technical solutions

- Transverse Porch all 4,00 m.
- Width of span 4,00 m or 6,00 m.
- Height under porch 2,50 m or 3,00 m.

Option Clip Alu FILCLAIR

- Preservation and mechanical protection of the technical textiles
- Equipment Solutions
The Screen shade FILCLAIR are smart climatic architectures..

Various solutions of equipment are proposed to you:

- Thermic Screen and of motorized mobile shade;
- System with cable or trammel.
- Trolley of irrigation.
- Pendular Irrigation.
- Micro-drops shower.

Technical textiles

- Wide range of climatic technical textiles.

- Shade net

• Insect proof system

• Aluminized textiles

• Polyester wire

< click to enlarge